



ITALTINTO

AUTOMATIC COLOR DISPENSER

i301 | ***i351***



AUTOMATIC COLOR DISPENSER

i301 | i351



OUR FLEXIBLE AND ROBUST ALL-AROUND DISPENSER TALENT

i301 / i351 is ITALTINTO's most advanced and reliable Tinting machine which can deliver higher productivity without any interventions. The sleek design of the machine delivers unprecedented flexibility and ease in operation. It is available in both Water-based and Solvent-based colorant systems. The i301 / i351 meets high standards of Accuracy and Repeatability. Its smart design ensures that this machine is easy to set up and operator-friendly.

TECHNICAL FEATURES

DISPENSING MODE	i301 Sequential i351 Simultaneous (up to six colorants)
ACCURACY	Down to 1/384. fl. oz. (0.077ml)
DISPENSING SPEED	i301 0.2 Ltr /min - i351 1.1 Ltr /min
NUMBER OF CANISTERS	Up to 16
CANISTER CAPACITY	3 Ltr
PUMP	Stainless steel 2. fl. oz. (60ml)
COLORANT STIRRING	Automatic
CAN SENSOR	Standard
CAN TARGET LIGHT	Yes
CAN HANDLING	Hydraulic can shelf
AUTOMATIC DROP STOP (Humidifier Auto Cap)	Standard
MAXIMUM CAN DIMENSIONS	380 W x 550 D x 390 H mm (15.0 W x 21.7 D x 15.4 H in)
COMPATIBILITY	Water / Universal / Solvent Based Colorants
POWER SUPPLY	Single Phase 110-120V / 220-240V
MACHINE NET WEIGHT	200kg (441lb)
MAXIMUM MACHINE SIZE	840 W x 900 D x 1560 H mm + Side Shelf 420 mm (33.1 W x 35.4 D x 61.4 H in + Side Shelf 16.5 in)
SHIPPING SIZE	1030 W x 920 D x 1760 H mm - Gross Weight 225 kg (40.6 W x 36.2 D x 69.3 H in) - Gross Weight 496 lbs
SAFETY	CE, cMETus, cCSAus compliance
SOFTWARE	ITALTINTO PRO.SCAN dispenser software
OPTIONS	Customized software solutions are available Connectivity of hardware for External software is available Fish Tail Mixing Technology Paint can puncher



WHY CHOOSE i301 / i351

- Simultaneous piston pump colorant dispensing
- Single motor controlling entire dispensing system
- No tubing system
- Low maintenance
- Low cost of operation and ownership



www.italtinto.com

¹⁾ Screen and computer peripherals shown for illustration only.

This information corresponds to the present state of our knowledge and is intended as a general description of our products and their possible applications. Italtinto makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Italtinto's products for its particular applications. *Nothing included in this information waives any of Italtinto's General Terms and Conditions of Sale, which control unless it agrees otherwise in writing. Any existing intellectual / industrial property rights must be observed. Due to possible changes in our products and applicable national and international regulations and laws, the status of our products could change. For additional information, please contact Italtinto.

ITALTINTO EUROPE SRL
☎ +39 02 90005234
sales.europe@italtinto.com

ITALTINTO EQUIPMENTS PVT. LTD.
☎ +91 9821507298
sales.amea@italtinto.com

ITALTINTO USA CORPORATION
☎ +1 980 329 8962
sales.na@italtinto.com

ITALTINTO LATIN AMERICA
☎ + 55 11 2698 0464
sales.latam@italtinto.com