



ITALTINTO

AUTOMATIC COLOR DISPENSER

i302 | ***i352***



AUTOMATIC COLOR DISPENSER

i302 | i352



THE PERFECT DISPENSING SOLUTION FOR MEDIUM TO PREMIUM RETAIL AND DIY OUTLETS

The appealing tall design of the i302 / i352 paired with engineering excellence adds great value to every retail environment. Its embedded rotating canister array makes refilling quick and easy, even in a confined paint booth.

i302 / i352 are free from tubing system and equipped with Automatic Drop Stop mechanism to prevent drying of colorants at Nozzles.

TECHNICAL FEATURES

DISPENSING MODE	i302 Sequential i352 Simultaneous (up to six colorants)
ACCURACY	Down to 1/384. fl. oz. (0.077ml)
DISPENSING SPEED	i302 0.2 Ltr /min - i352 1.1 Ltr /min
NUMBER OF CANISTERS	Up to 16
CANISTER CAPACITY	3 Ltr
PUMP	Stainless steel 2. fl. oz. (60ml)
COLORANT STIRRING	Automatic
CAN SENSOR	Standard
CAN TARGET LIGHT	Yes
CAN HANDLING	Hydraulic can shelf
AUTOMATIC DROP STOP (Humidifier Auto Cap)	Standard
MAXIMUM CAN DIMENSIONS	380 W x 550 D x 390 H mm (15.0 W x 21.7 D x 15.4 H in)
COMPATIBILITY	Water / Universal / Solvent Based Colorants
POWER SUPPLY	Single Phase 110-120V / 220-240V
MACHINE NET WEIGHT	270kg (595lb)
MAXIMUM MACHINE SIZE	800 W x 800 D x 1600 H mm (31.5 W x 31.5 D x 63.0 H in)
SHIPPING SIZE	1030 W x 920 D x 1760 H mm - Gross Weight 290 kg (40.6 W x 36.2 D x 69.3 H in) - Gross Weight 639 lbs
SAFETY	CE
SOFTWARE	ITALTINTO PRO.SCAN dispenser software
OPTIONS	Customized software solutions are available Connectivity of hardware for External software is available Fish Tail Mixing Technology



WHY CHOOSE i302 / i352

- Rotating canister array for easy front colorant refilling
- Simultaneous colorant dispensing
- Single motor controlling entire dispensing system
- No tubing system
- Low maintenance
- Low cost of operation and ownership



www.italtinto.com

¹Screen and computer peripherals shown for illustration only.

This information corresponds to the present state of our knowledge and is intended as a general description of our products and their possible applications. Italtinto makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Italtinto's products for its particular applications. *Nothing included in this information waives any of Italtinto's General Terms and Conditions of Sale, which control unless it agrees otherwise in writing. Any existing intellectual / industrial property rights must be observed. Due to possible changes in our products and applicable national and international regulations and laws, the status of our products could change. For additional information, please contact Italtinto.

ITALTINTO EUROPE SRL
☎ +39 02 90005234
sales.europe@italtinto.com

ITALTINTO EQUIPMENTS PVT. LTD.
☎ +91 9821507298
sales.amea@italtinto.com

ITALTINTO USA CORPORATION
☎ +1 980 329 8962
sales.na@italtinto.com

ITALTINTO LATIN AMERICA
☎ + 55 11 2698 0464
sales.latam@italtinto.com

Charlotte, USA | Mumbai, India | Milan, Italy | Sao Paulo, Brazil