



ITALINTO

AUTOMATIC COLOR DISPENSER

i253C | ***i256C***



AUTOMATIC COLOR DISPENSER

i253C | *i256C*



The Perfect Dispensing Solution For Medium To Premium Sized Retail and DIY Outlets

The i253C - i256C combines cutting-edge dispenser technology with eye-catching design adding value for every paint shop. Its embedded rotating canister array makes refilling quick and easy, even in a confined paint booth. The high canister capacity optimizes high-speed dispensing of up to 18 colorants.

TECHNICAL FEATURES

DISPENSING MODE	Simultaneous (up to six colorants) with piston pumps
ACCURACY	Down to 1/384 fl. oz. (corresponding to 0.077 ml)
DISPENSING SPEED	Up to 1.1 Ltr/min
NUMBER OF CANISTERS	Up to 18 (standard up to 16)
CANISTER CAPACITY	i253C: 3 Ltr i256C: 6 Ltr
PUMP	Stainless steel 2 fl. oz. or 4 fl. oz. (only for i256C) (corresponding to 60 ml or 120 ml)
COLORANT STIRRING	Fish Tail Mixing Technology
CAN SENSOR	Standard
CAN TARGET LIGHT	No
CAN HANDLING	Manual can shelf
AUTOMATIC DROP STOP	Standard
MAXIMUM CAN DIMENSIONS	380 W x 450 D x 410 H mm (15.0 W x 17.7 D x 16.1 H in)
COMPATIBILITY	Water-based colorants
POWER SUPPLY	Single Phase 110 – 120 V / 220 – 240 V
MACHINE NET WEIGHT	i253C: 184 kg (405.6 lb) i256C: 200 kg (440.9 lb)
MAXIMUM MACHINE SIZE	975 W x 774 D x 1424 H mm (38.4 W x 30.5 D x 56.1 H in)
SHIPPING SIZE	1100 W x 900 D x 1715 H mm (43.3 W x 35.4 D x 67.5 H in)
SAFETY	CE
SOFTWARE	ITALTINTO PRO.SCAN dispenser software
OPTIONS	Customized software solutions are available. Hardware interfacing software on request. Solvent-based preparations and other liquids on request.



WHY CHOOSE THE i253C - i256C

- Small footprint.
- High canisters capacity (**i256C**).
- Rotating canister array for easier front colorant refilling.
- Single motor controlling entire dispensing system.
- No tubing - colorant is dispensed directly.
- Low maintenance.
- Low cost of operation and ownership.

¹⁾Screen and computer peripherals shown for illustration only.

This information corresponds to the present state of our knowledge and is intended as a general description of our products and their possible applications. Italtinto makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Italtinto's products for its particular applications. *Nothing included in this information waives any of Italtinto's General Terms and Conditions of Sale, which control unless it agrees otherwise in writing. Any existing intellectual / industrial property rights must be observed. Due to possible changes in our products and applicable national and international regulations and laws, the status of our products could change. For additional information, please contact Italtinto.



ITALTINTO EUROPE SRL
Via Zibido,3 20080
Zibido San Giacomo,
Milano, ITALY
sales.europe@italtinto.com
www.italtinto.com

**COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =**

Cleveland, USA | Mumbai, India | Milan, Italy | Sao Paulo, Brazil