



ITALTINTO

COLOR MIXER  
**im3200**



# COLOR MIXER

## *im3200*



### DURABLE MIXER WITH GREAT ERGONOMICS

The im3200 is ITALTINTO's latest addition to its paint mixer family. The im3200 is specifically designed for use with hard-to-mix highly viscous paints. It is a simple and durable mixer with great ergonomics and ease of use. The im3200 is equipped with a front load roller which makes the unit easy to load. It also comes with a slotted rubber bottom plate for easy can centering and solid container support. This unit is also available in a roller line configuration with metal bottom plate and built in bail handle support.



#### Technical Features

TYPE	Gyroscopic
MAXIMUM CAN HEIGHT	400 mm
CLAMPING CLEARANCE	407 mm
MINIMUM CAN HEIGHT	70 mm
MAXIMUM CAN DIAMETER	340 mm
CAN CLAMPING	Manual
CAN HOLDER ASSEMBLY LOCK	Available
DOOR	Plastic Shutter with Metal bars for safety
EMERGENCY SWITCH	Available
DOOR LOCK WHILE RUNNING	Available
TIMER	Mechanical (up to 6 min)
ROTATION DIRECTION	Anti - Clockwise
MAIN MOTOR	1 HP, 1425 rpm, (230V) or 1725 rpm (115V)
SPEED	Single Speed
RPM	can holder assembly - 100 rpm Bottom Plate - 200 rpm
MAXIMUM NOISE LEVEL	55 db
POWER SUPPLY	220 V / 50 Hz 110 V / 60 Hz
MAXIMUM MACHINE SIZE	900 W x 810 D x 1210 H mm
MACHINE NET WEIGHT	200 Kg
SHIPPING SIZE	950 W x 850 D x 1375 H mm
GROSS WEIGHT	235 Kg
OPTIONS	Customised color combinations Unique paint spill containment system with spill catch and drain spout for easy cleanup

#### Why choose im3200

- Robust & most durable machine.
- Built-in cycle counter located on internal board
- Low maintenance
- Reinforced sliding door for easy access and improved durability
- Improved built-in voltage fluctuation protection



[www.italtinto.com](http://www.italtinto.com)

This information corresponds to the present state of our knowledge and is intended as a general description of our products and their possible applications. Italtinto makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Italtinto's products for its particular applications. \*Nothing included in this information waives any of Italtinto's General Terms and Conditions of Sale, which control unless it agrees otherwise in writing. Any existing intellectual / industrial property rights must be observed. Due to possible changes in our products and applicable national and international regulations and laws, the status of our products could change. For additional information, please contact Italtinto.

**ITALTINTO EUROPE SRL**  
 ☎ +39 02 90005234  
[sales.europe@italtinto.com](mailto:sales.europe@italtinto.com)

**ITALTINTO EQUIPMENTS PVT. LTD.**  
 ☎ +91 9821507298  
[sales.amea@italtinto.com](mailto:sales.amea@italtinto.com)

**ITALTINTO USA CORPORATION**  
 ☎ +1 980 329 8962  
[sales.na@italtinto.com](mailto:sales.na@italtinto.com)

**ITALTINTO LATIN AMERICA**  
 ☎ + 55 11 2698 0464  
[sales.latam@italtinto.com](mailto:sales.latam@italtinto.com)