

AUTOMATIC COLOR DISPENSER i 250N | i 250C



_

ITALTINTO

i250N i250C

THE PERFECT ENTRY LEVEL DISPENSER TO MATCH ALL YOUR COLOR NEEDS

The i250N / i250C is one of the most compact machines available on the market with simultaneous colorant dispensing mode (only 0.65m² Footprint). It saves shop space without losing performance and accuracy.

TECHNICAL FEATURES	
DISPENSING MODE	i250C: Simultaneous (up to six colorants) with piston pump i250N: Simultaneous (up to six colorants) with piston pump
ACCURACY	Down to 1/384 fl. oz. (corresponding to 0.077 ml)
DISPENSING SPEED	1.1 Ltr/min
NUMBER OF CANISTERS	Up to 16 (i250C: 12)
CANISTER CAPACITY	3 Ltr
PUMP	Stainless steel 2 fl. oz. (corresponding to 60 ml)
COLORANT STIRRING	Automatic
CAN SENSOR	Standard
CAN HANDLING	Manual can shelf
AUTOMATIC DROP STOP	Standard
MAXIMUM CAN DIMENSIONS	380 W x 450 D x 410 H mm (15.0 W x 17.7 D x 16.1 H in)
COMPATIBILITY	Water-based colorants
POWER SUPPLY	Single Phase 110–120V / 220–240V
MACHINE NET WEIGHT	i250C: 160 kg (352.7 lb) i250N: 170 kg (374.7 lb)
MAXIMUM MACHINE SIZE	792 W x 810 D x 1430 H mm (38.4 W x 31.9 D x 56.3 H in)
SHIPPING SIZE	1100 W x 900 D x 1715 H mm (31.2 W x 35.4 D x 67.5 H in)
SAFETY	CE
SOFTWARE	ITALTINTO PRO.SCAN dispenser software
OPTIONS	Customized software solutions are available
	Hardware interfacing software on request
	Solvent-based preparations and other liquids on request
	Fish Tail Mixing Technology
	Open frame design for easy dispensing view and can position



WHY CHOOSE THE i250N - i250C

- Small footprint.
- Rotating canister array for easier front colorant refilling.
- Single motor controlling entire dispensing system.
- No tubing colorant is dispensed directly.
- Low maintenance.
- Low cost of operation and ownership.



Screen and computer peripherals shown for illustration only.

This information corresponds to the present state of our knowledge and is intended as a general description of our products and their possible applications. Italtinto makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Italtinto's products for its particular applications. *Nothing included in this information waives any of Italtinto's General Terms and Conditions of Sale, which control unless it agrees otherwise in writing. Any existing intellectual / industrial property rights must be observed. Due to possible changes in our products and applicable national and international regulations and laws, the status of our products could change. For additional information, please contact Italtinto.



ITALTINTO EUROPE SRL

Via Zibido,3 20080 Zibido San Giacomo, Milano, ITALY

sales.europe@italtinto.com www.italtinto.com

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =